

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MEGALACK FAST HS CLEARCOAT
Product code : L0090638

1.2 Relevant identified uses of the substance or mixture and uses advised against

Chemical nature : Liquid solution

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA
Via Cecilio 17
22100 Como
Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.eu
Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299
This telephone number is available during office hours only (8:00-18:00).

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Harmful	R20/21: Harmful by inhalation and in contact with skin.
Irritant	R38: Irritating to skin.
Dangerous for the environment	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2 Label elements

Labelling according to EC Directives (1999/45/EC)

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

Hazard pictograms

:



Highly
flammable

Harmful

R-phrases(s)

: R11
R20/21

Highly flammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R38
R52/53

S-phrases(s)

: S 9
S16

S33

S36/37

S60

Keep container in a well-ventilated place.
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.
Wear suitable protective clothing and gloves.
This material and its container must be disposed of as hazardous waste.

Hazardous components which must be listed on the label:

- 1330-20-7 xylene

Sensitising components

: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
May produce an allergic reaction.

2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

3. Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Liquid solution

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
xylene	1330-20-7 215-535-7 01- 2119488216- 32	R10 Xn; R20/21 Xi; R38	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 20 - < 25

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

ethyl acetate	141-78-6 205-500-4 01- 2119475103-46	F; R11 Xi; R36 R66 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	< 10
Low boiling point naphtha - unspecified	64742-95-6 265-199-0 01- 2119455851-35	R10 Xi; R37 N; R51/53 Xn; R65 R66 R67	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304	>= 2,5 - < 10
1,2,4-trimethylbenzene	95-63-6 202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51-R53	Flam. Liq. 3; H226 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Aquatic Chronic 2; H411	< 2,5
Siloxanes and silicones, di-Me, 3-hydroxypropyl Me, ethers with polyethylene glycol mono-Me ether	68938-54-5	Xn; R20 N; R51/53	Acute Tox. 4; H332 Aquatic Chronic 2; H411	< 2,5
1,3,5-trimethylbenzene	108-67-8 203-604-4	R10 Xi; R37 N; R51-R53	Flam. Liq. 3; H226 STOT SE 3; H335 Aquatic Chronic 2; H411	< 2,5
cumene	98-82-8 202-704-5	R10 Xn; R65 Xi; R37 N; R51-R53	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 Aquatic Chronic 2; H411	< 2,5
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7 255-437-1	Xi; R43 N; R50/53	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
WEL substance :				
n-butyl acetate	123-86-4 204-658-1 01- 2119485493-29	R10 R66 R67	Flam. Liq. 3; H226 STOT SE 3; H336	>= 15 - < 20

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

4. First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|--|
| General advice | : When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person. |
| If inhaled | : Remove to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious place in recovery position and seek medical advice. |
| In case of skin contact | : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place |
| In case of eye contact | : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Seek medical advice.
Put eye-washer on working place
Remove contact lenses. |
| If swallowed | : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Keep at rest. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|-----------------------------|
| Symptoms | : No information available. |
| Risks | : No information available. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--|
| Treatment | : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
Seek medical advice. |
|-----------|--|

5. Fire-fighting measures

5.1 Extinguishing media

- | | |
|------------------------------|---|
| Suitable extinguishing media | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray. |
| Unsuitable extinguishing | : Do NOT use water jet. |

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.
Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.
Clean contaminated surface thoroughly.
Dam up.
Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

7. Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding of the given occupational exposure limits (see section 8).
Use only in area provided with appropriate exhaust ventilation.
Avoid contact with skin, eyes and clothing.
Smoking, eating and drinking should be prohibited in the application area.
Avoid inhalation of vapour or mist.
For personal protection see section 8.
Thoroughly mix before using
After using, store in a well-sealed container
- Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Solvent vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Electrical installations / working materials must comply with the technological safety standards.
Keep away from sources of ignition - No smoking.
Store between 5 ° an 35 °C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

7.3 Specific end uses

- : This information is not available.

8. Exposure controls/personal protection

8.1 Control parameters

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

Components	CAS-No.	Value	Control parameters	Update	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
n-butyl acetate (Vapour and gas)	123-86-4		150 ppm 713 mg/m3		
			200 ppm 950 mg/m3		
ethyl acetate	141-78-6		400 ppm 1.400 mg/m3		
Solvent naphtha (petroleum), light arom.	64742-95-6		50 ppm 100 mg/m3		
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm 100 mg/m3	2000-06-16	2000/39/EC
Further information	:	Indicative			
mesitylene	108-67-8	TWA	20 ppm 100 mg/m3	2000-06-16	2000/39/EC
Further information	:	Indicative			
cumene	98-82-8	TWA	20 ppm 100 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	50 ppm 250 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			

DNEL

n-butyl acetate

: End Use: Professional use
Exposure routes: Skin contact
Potential health effects: Local effects
Exposure time: 8 h
Value: 7 ppm

End Use: Professional use
Exposure routes: Inhalation
Potential health effects: Local effects
Value: 48 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

PNEC
n-butyl acetate : Water
Value: 0,18 mg/l

Soil
Value: 0,093 mg/kg

8.2 Exposure controls

Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.

Hand protection : For prolonged or repeated contact use protective gloves.
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin should be washed after contact.
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.
Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.
Personnel should wear protective clothing
Workers should wear antistatic footwear.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Flash point : 0 - < 21 °C

Vapour pressure : 1 hPa
at 50 °C

Density : 0,9904 g/cm³

Flow time : 44 s

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

4 mm

Method: ASTM D 1200 '82

9.2 Other information

Solids by weight : 47,77 %

Volatile organic compounds : 52,23 %
(VOC) content

10. Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects., Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.,

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

- Inhalation of airborne droplets may cause irritation of the respiratory tract.
- Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
- Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Components:

xylene :

- Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

12. Ecological information

12.1 Toxicity

- Toxicity to fish :
Remarks:
No data is available on the product itself.

12.2 Persistence and degradability

- Biodegradability : Remarks:
no data available

12.3 Bioaccumulative potential

- Bioaccumulation : Remarks:
no data available

12.4 Mobility in soil

- Mobility : Remarks:
no data available

12.5 Results of PBT and vPvB assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6 Other adverse effects

Additional ecological information	: The product contains dangerous substances for the environment (see chapter n° 3). The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.
-----------------------------------	--

13. Disposal considerations

13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

ADR

UN number	: 1263
Transport hazard class(es)	: 3
Packing group	: II
Classification Code	: F1
Hazard identification No	: 33
Labels	: 3
Environmentally hazardous	: no

IATA

UN number	: 1263
Description of the goods	:
Class	: 3
Packing group	: II
Labels	: 3
Environmentally hazardous	: no

IMDG

UN number	: 1263
Description of the goods	:
Class	: 3
Packing group	: II
Labels	: 3
EmS Number 1	: F-E
EmS Number 2	: S-E

Marine pollutant	: no
------------------	------

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Risk classification according to VbF : Flash point less than 21 °C, at 15 °C not miscible in water

Water contaminating class (Germany) : highly water endangering
VWVWS A4

Other regulations : The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

15.2 Chemical Safety Assessment

No data is available on the product itself.

16. Other information

Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitization by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51	Toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under sections 2 and 3.

SAFETY DATA SHEET

according to Regulation (EC) No. 453/2010

MEGALACK FAST HS CLEARCOAT

Version 1.0

Revision Date 25.10.2012

Print Date 05.11.2012

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.